

TRANSPORTATION PERMIT CONDITIONS

(8/2013)

POSSESSION OF PERMIT:

This permit shall be carried in the vehicle or combination of vehicles to which it refers and shall be open to inspection by any peace officer, traffic officer, authorized agent of the City of Fullerton, or any other officer or employee charged with the care and protection of such highways (C.V.C. 35783).

Permit Conditions:

1. Validity of Permit

This permit is valid only for movement on the assigned City streets and highways. This permit is NOT VALID on State highways and overcrossings under the jurisdiction of the State of California Department of Transportation.

2. Void Permit

This permit is null and void and hereby declared non-existent

- a. if any portion, part or section is illegible;
- b. if it is not signed by an authorized representative of the City of Fullerton;
- c. if any portion, part or section has been altered or if an attempt to alter is apparent;
- d. if used to represent proper authority for carrying a load and/or moving a vehicle which is not specifically named or organizationally related to the company, agency, or firm to which the permit was issued;
- e. if used to present proper authority for carrying a load or moving a vehicle by any company, crew or equipment not specifically named or organizationally related to the company, agency, or firm to which the permit was issued;
- f. if presented without the attachments firmly affixed that are specifically named and required upon the face of the permit;
- g. if used to represent proper authority for carrying a load or moving a vehicle before and/or after the times and dates authorized.

3. Permittee Agreement

Acceptance of this permit constitutes an agreement by the permittee to observe and comply with all of the general and specific conditions on the face of the permit and attachments thereto.

The use of this permit is prima facie evidence that the driver has checked the load and/or vehicle and knows it to be within the limits as set forth hereon and has verified the routing accuracy. The vehicle and/or load authorized under this permit is subject to inspection by representatives of the City of Fullerton and cost of such inspection shall be borne by the permittee.

4. Repair of Damage

In accepting this permit, the permittee agrees to repair at his own expense and to the satisfaction of the Director of Public Works, any damage to highway appurtenances or structures. Notwithstanding, work or repair may be done by City of Fullerton forces at the option of the Director of Public Works, the cost to be borne by the permittee. In the event of damage to City facilities such as bridges, traffic signals, light standards and other appurtenances, a written report must be filed with the City within 72 hours after such damage has been done. Failure to make this report will be considered cause for cancellation of all permit privileges pending a satisfactory arrangement with the City for repair or replacement of the damaged facility.

5. Liabilities

The permittee is responsible for all liability for injury to, or death of any person, or damage to property which may occur through any act or omission of either the permittee or the City of Fullerton arising from the issuance of this permit. In the event any claim, suit or action is brought against the City of Fullerton, its officers, employees or agents thereof, by reason of, or in connection with any such act or omission, permittee shall defend, indemnify and hold harmless the City, its officers, employees or agents from such claim, suit or action.

6. Overhead Clearance

When height of load exceeds legal limit, it becomes the responsibility of the permittee to check all underpasses, bridges, overhead wires or other such structures for impaired vertical clearance and to bypass or arrange clearance at such locations.

7. Reducible Loads

This permit is issued for the movement of an "Extralegal Load" as defined in C.V.C. 320.5 when loaded at its least dimensions.

This permit is automatically canceled if the permitted dimensions and weight can be reduced to legal limits by repositioning and/or practical removal of a part, portion, or unit therefrom.

Other items may be hauled provided they do not exceed the dimensions of the vehicle or permitted item and the loaded vehicle is of legal axle and gross weights.

Overheight permits shall not be issued for items transported on a conventional flat deck trailer unless the deck is needed to support a long fragile load or a long load that would cause unbalanced axle group weights.

8. Tire Capacity

Permitted axle or axle group weights shall not exceed the rated capacity of vehicle tires except as allowed by the Title 13, Article 14, Section 1085 of the California Administrative Code. After January 1, 1988, said weights shall not exceed the rated capacity of the vehicle tires.

9. Booster Type Axles

A booster axle is an axle, generally, having an air or hydraulic cylinder suspension system that can be actuated independently to assume a portion of the weight that would otherwise be carried by adjacent axles. Booster axles and add-on or "Joe Dog" axles shall not be used in the movement of overweight permit loads.

10. Traveled Way

Where practical, the vehicle shall be kept in the far right lane of the highway and shall not encroach on highway shoulders except where necessary to allow trailing traffic to pass.

11. Movement During Darkness

"Darkness" is defined in Section 280 of the C.V.C. as being "...any time from one-half hour after sunset to one-half hour before sunrise...". Reference to "sunset" and/or "sunrise" on the face of the permit includes this said one-half hour grace period before and after sunrise and sunset. Movement is not allowed when visibility is less than 1,000 feet.

12. 3 a.m. Early Morning Movement

Any vehicle combination eligible for across the counter permit application may be issued a permit to begin movement at 3 a.m. These applications include:

- a. vehicles/loads up to 14'-0" width (14'-6" for qualified construction equipment);
- b. vehicles up to 135'-0" in combination length;
- c. vehicles up to bonus purple axle weight; and,
- d. vehicles with unlimited vertical height.

The following conditions will apply:

- a. The movement shall begin on any route shown on the current Overlimit Permit Route Map;
- b. Movement shall not start before 3 a.m.;
- c. Single trip permits or repetitive permits may be issued;
- d. Pilot Car requirements will apply for the routes authorized;
- e. Weekend movement is not authorized unless the vehicle/load qualifies for weekend movement;

13. Peak Hour Movement

Movements of "Extralegal Loads" are not permitted between 7:00 and 8:30 a.m. and 4:00 and 6:00 p.m.

14. Holiday Movement

Unless authorized on the face of this permit, movement is prohibited on the following holidays (or any of these holidays falling on a weekend celebrated on a weekday):

New Year's Day
President's Day
Memorial Day
Independence Day
Labor Day
Thanksgiving Day/Weekend
Christmas Eve/Day

When one of the above listed holidays falls on Monday or Friday, permit movements will not be allowed on the holiday nor the immediately preceding or following weekend, unless authorized on the face of the permit.

Restriction on the time of move may be imposed on certain highways where, due to a holiday, a substantial increase in traffic volume is recorded. Alternate routes should be used where available.

15. Movement in Inclement Weather

Movement shall not occur in snow, fog, rain or wind when visibility is restricted to less than 1,000 feet. Movement is prohibited when road surfaces are hazardous due to rain, ice, snow, or frost, or when use of tire chains is mandatory. No moving shall be done when the velocity of the wind is such that it causes the vehicle being towed to whip or swerve from side-to-side or fail to follow substantially in the path of the towing vehicle. Any accident caused by excessive wind or weather conditions shall be considered a prima facie violation of this condition.

16. Load Signs

All loads or vehicles being moved on City streets which exceed 8'-6" in width, 80' in length, or more than 10' of overhang shall display appropriate warning signs.

Signs shall be posted on front and rear and shall read "LONG LOAD" or "OVERSIZE." The "LONG ROAD" sign shall be used whenever overall length exceeds 100 feet. The "OVERSIZE" sign shall be used for shorter lengths and other oversize features. The more definitive signs reading "WIDE LOAD", "LONG LOAD", "OVERSIZE LOAD", "EXCESSIVE FRONT OVERHANG", or "EXCESSIVE REAR OVERHANG" may be substituted for the "OVERSIZE" sign when appropriate. The "LONG LOAD" sign shall have preference when length exceeds 100 feet and other oversize features exist. The lettering shall be a 10-inch minimum height with a 1-5/8-inch minimum brush stroke, and a minimum 1-inch margin all around. All signs shall be black letters on a yellow background, mounted at least 18 inches above the road surface front and rear. Signs shall be neat, clean, legible, mounted securely and visible from straight ahead or behind and to 45-degrees either side thereof.

17. Pilot Car and Equipment

It shall be the responsibility of the permittee to ensure that pilot car vehicles and operators are equipped and briefed as to their duties prior to movement. Pilot cars shall be single vehicle with a minimum 60 inches in width, and may operate with

A non-destructive vertical clearance measuring device with height in excess of 14 feet.

Pilot cars shall be equipped with:

- a. one each STOP/SLOW sign paddle;
- b. one each orange vest, shirt or jacket;
- c. one each red hand flag (18" x 18" minimum);
- d. two-way radio communication between the pilot car(s) and the transporting vehicle;
- e. top-mounted flashing amber warning light(s). The light(s) shall be visible to the front when leading and to the rear when following, and shall be operated at all times when escorting a permit move. Lights shall be removed or covered with opaque material when not escorting movement described;
- f. neat, clean, legible sign(s) visible from straight-ahead or behind and to 45-degrees either side thereof. The bottom of the sign(s) shall be a minimum of 48 inches above the ground. The sign shall read "OVERSIZE" when viewed from the front or rear. The more definitive signs reading "OVERSIZE LOADS", "WIDE LOAD", or "LONG LOAD" may be substituted for the "OVERSIZE" sign when appropriate. The sign shall have a bright yellow background with black lettering and have a minimum projected area of 440 square inches. The letter shall have one-inch minimum brush stroke with a six-inch minimum project letter height.

18. Pilot Car Location and Responsibility

When required, the permit shall list all highways where pilot car(s) are required. A pilot car shall:

- a. precede the load on two or three-lane conventional roads and follow on four or more lane conventional highways and divided highways. When two pilot cars are required, one shall precede and one shall follow;
- b. remain right of the centerline of the roadway at all times except when prevented by the physical limitations of the highway. The use of a pilot car does not grant to the permittee the right to pre-empt the opposing traffic lane. When it becomes necessary because of physical limitations of the highway to use a portion of the opposing traffic lane, the permit move shall not occupy that lane until it has

been advised by the pilot car that the lane is clear of all on-coming traffic. Opposing traffic is not to be stopped, except in extreme emergencies. It shall be the responsibility of the permit holder to stop safely and wait until the opposing lane is free of traffic before proceeding.

- c. maintain proper interval between load and the pilot car to allow passing by other traffic;

A pilot car shall not;

- a. pre-empt opposing traffic;
- b. tow another vehicle while being used as a pilot car;
- c. display the STOP/SLOW sign paddle out of the window of a moving vehicle;
- d. stop opposing traffic except in extreme emergencies;
- e. convoy more than one load at the same time;

When necessary to post a flagger in order to warn and direct traffic, the flagging shall be done in accordance with Title 8, Sections 1598 and 1599 of the California Division of Occupational Safety and Health Construction Safety Orders and Caltrans "Manual of Traffic Controls". Flaggers shall not be less than 18 years of age.

19. Manufactured Housing Axle Weight

Axle weights for "Manufactured Housing" (C.V.C. 387) shall not exceed 6,000 lbs. per axle.

20. Manufactured Housing – Tow Vehicle

Tractor units towing manufactured housing as defined in C.V.C. 387 that exceed legal width and up to 12 feet in widths shall be equipped with dual rear wheel and shall have an unladen weight as defined in C.V.C 660 of not less than 9,500 lbs.